




# FilaPrint PLA MATT

FilaPrint PLA MATT is an easy to print variant on the everyday material PLA, with an aesthetical matt effect. Its surface diffuses light to give it a matt look, and creates a rough feeling. This material can be printed on most common printers and has a reliable bed adhesion to most common build plate materials.

## Material features:

- Matt effect, low light refraction
- Easy to print rough surface
- Reliable bed adhesion
- Improved printing speed compared to PLA



## Colours:

PLA MATT is available from

stock in 3 colours.

## Filament specs.

Size	Ø tolerance	Roundness
1,75mm	± 0,05mm	≥ 95%
2,85mm	± 0,10mm	≥ 95%

## Material properties

Description	Testmethod	Typical value
Specific gravity	ISO 1183	1,38 g/cc
MFR 210°C/2,16 kg	ISO 1133	14 gr/10 min
Tensile Strength at Yield (MPa)	ISO 527	46,6 Mpa
Strain at yield	ISO 527	2,1%
E-Modulus	ISO 527	3973 Mpa
Printing temp.	DF	215±10°C

## Additional info:

Due to its low tendency to warp PLA MATT can also be printed without a heated bed. If you have a heated bed the recommended temperature is ± 35-60°C.

PLA MATT can be used on all common desktop FDM or FFF technology 3D printers.

Storage: Cool and dry (15-25°C) and away from UV light. This enhances the shelf life significantly.